

Customer Information:

Organization	Contact Person
Address	Project
	Mobile
	Email ID

Valve Specification:

Media Handled: Coal Ash Powder Granules Others (Specify)

Others:

Nature of media: Abrasive Corrosive Hygroscopic Sticky

Application: Isolation Gravity discharge Pneumatic conveying
Airlock Gravity Feed

Opening/Valve (s) size:mm Inch Round port Square Port

Valve (s) Installation: Inside Outside

Service requirements: Main valve Maintenance valve Modulating

Bulk density (Kg/m³): Particle sizing (mm):

Maximum load on gate (Kg):

Temperature (°C): Operating: Design:

Pressure (Bar): Operating: Design:

Valve pressure rating: PN3 (45 PSI) PN5 (70 PSI)

Valve actuation: Hand wheel Hand lever Chain wheel
Pneumatic Motorized Hydraulic

Other actuation:

Valve mounting position: Horizontal Vertical Inclined

Other Information:

Dust cover required: Yes No

Flange mounting standard: ASME B16.5/16.47 EN 1092 PN10

Others (Specify):

Zone classification: Hazardous Non hazardous
Zone 1 Zone 2 Zone 3

Supply voltage (volts-Hz):

Control voltage (volts-Hz):

Optional features (Specify):



JASH ENGINEERING LTD
 31, Sector C, Industrial Area, Sanwer Road,
 Indore – 452 015 (M.P.), INDIA
 Ph: +91-731-6732700, 2720143, 2721143
 Email: info@jashindia.com
 Website: www.jashindia.com

- SUBSIDIARIES:**
- Rodney Hunt Inc. USA
 - Mahr Maschinenbau GmbH, Austria
 - Shivpad Engineers Pvt Ltd, India
 - Engineering & Manufacturing Jash Ltd, Hong Kong.